



- ✓ Additional Wired Controller
- ✓ High Efficiency
- ✓ Self Diagnosis
- ✓ 1W standby
- ✓ Valve Protection Cover
- ✓ Heating operating temperature range -20°C
- ✓ Cooling operating temperature range -15°C
- ✓ Condenser and Compressor's Heaters
- ✓ Built-in Drain Pump
- ✓ 360° Air Flow Panel

Model		ACP-09CCIFM25AERI	ACP-12CCIFM35AERI	ACP-18CCIFM50AERI	
Capacity	Cooling	2640 W	3520 W	5280 W	
	Heating	2930 W	4100 W	5280 W	
Refrigerant		R410A	R410A	R410A	
Airflow		≤580 m <sup>3</sup> /h	≤650 m <sup>3</sup> /h	≤800 m <sup>3</sup> /h	
Dehumidifying capacity		1.0 L/h	1.2 L/h	1.8 L/h	
Sound pressure level	Indoor unit	≤39.0 dB(A)	≤41.0 dB(A)	≤48.0 dB(A)	
Sound power level	Indoor unit	≤53 dB	≤58 dB	≤59 dB	
Outer Diameter of Liquid Pipe		1/4"	1/4"	1/4"	
Outer Diameter of Gas Pipe		3/8"	3/8"	1/2"	
Connection wire		4x1.00 mm <sup>2</sup>	4x1.00 mm <sup>2</sup>	4x1.00 mm <sup>2</sup>	
Power supply		~220-240V/1/50Hz; Outdoor unit			
<b>Working range</b>		<b>-20°C ≤ T ≤ 50°C</b>	<b>-20°C ≤ T ≤ 50°C</b>	<b>-20°C ≤ T ≤ 50°C</b>	
Net dimensions	Indoor unit	570×570×260 mm	570×570×260 mm	570×570×260 mm	
Net weight	Indoor unit	14.5 kg	16.0 kg	18.0 kg	
	Panel	2.5 kg	2.5 kg	2.5 kg	